



ECONOMY MATERIALS HANDLING RESILIENT

ECOSOLID **Pneumatic Shaped Solid**

Ecosolid is an entry-level solid tire option available in the 8" to 15" rim size range. It is designed for use on forklifts in light-duty application.

Ecosolid's updated manufacturing platform and tighter production control now deliver improved performance.

FEATURES

- Available in standard black compound
- Steel-reinforced base
- Wear indicator built in to lug design

*Testing results concluded from TWS field-testing program.

ECONOMY MATERIALS HANDLING RESILIENT

ECOSOLID

Tire Size	Alternative Size	Rim Size	Tire Dimensions (in)		Load Capacity (lbs)			Weight (lbs)
			Overall Diameter	Section Width	Static	Forklift Trucks up to 15 mph		
						Load Wheel	Steering Wheel	
5.00-8		3.00D-8	18.0	4.8	3,640	3,120	2,405	31
6.00-9		4.00E-09	20.0	5.5	4,830	4,155	3,195	52
6.50-10		5.00F-10	22.0	6.4	5,995	5,160	3,970	72
7.00-12		5.00S-12	26.0	6.6	7,450	6,435	4,940	94
8.25-15		6.5-15	31.0	8.1	12,145	10,470	8,045	166
28x9-15	225/75-15 (8.15-15)	7.0-15	27.0	8.0	8,820	7,595	5,840	118
250-15	250/70-15	7.0-15	28.0	8.5	12,145	10,460	8,045	134
300-15	315/70-15	8.0-15	32.0	10.0	14,980	12,895	9,920	223

AVAILABLE COMPOUNDS

Standard
Black

TREAD PATTERNS



Ecosolid

Dealer Logo

Dealer Address and
contact information
WWW.TRELLEBORG.COM/WHEELS