


Structure

- Steel plated, rim consisting out of 2 halves, supplied along with the existing bolts, nuts and washers.

Possibility for other dimensions, ask your contact (also see "rim technical fill out form")



Rim width (B1)	Rim diameter (D1)	Tyre size	Centre-hole (D2)	Pitch-circle (C)	No. of holes (G)	Ø of studholes	Flange-position (L1)	Used for	REF
2.50	4	4.00-4	52	68	5	8,0	Half	Komatsu - Pimespo - OM	129TA7548
3.00 D	8	4.00-8	85	130	5	19,0	Half	Clark	129TA7549
		5.00-8	110	140	5	18,5	Half	Hyster	129TA7550
		125/75-8	86	114	6	15,0	Half	Toyota	107TA5381
		15x4.5-8	100	125	6	16,0	Half	Divers	107TA5382
			110	148	6	15,0	Half	Divers	107TA5380
4.33 R	8	16x6-8	95	135	5	17,5	124	Divers	129TA7551
		105/75-8	110	145	5	18,5	Half	Hyster	129TA7552
		18x7-8	110	147	5	17,5	122	Divers	107TA5384
		180/70-8	90	130	6	17,5	89	Divers	107TA5385
			96	136	6	17,5	121	TCM	129TA7553
			100	140	6	17,5	50	Komatsu	107TA5383
			105	142	6	18,0	Half	Toyota	129TA7554
4.00 E	9	6.00-9	124	165	5	17,0	Half	Yale - Hyster	129TA7555
		140/55-9	140	170	6	18,0	Half	Divers	129TA7556
			150	180	6	18,0	Half	Divers	107TA5387
			130	160	8	16,5	Half	Divers	107TA5386
			142	170	8	16,0	Half	Divers	107TA5388
5.00 F	10	6.50-10	127	165	5	16,0	Half	Yale - Hyster	129TA7557
		7.0/85-10 IMPL.	140	170	6	18,0	Half	Divers	129TA7558
			150	180	6	18,0	Half	Daewoo	129TA7559
			150	180	6	18,0	Half	Divers	107TA5390
			170	200	6	17,0	Half	Caterpillar	129TA7560
			130	160	8	17,0	Half	TCM	107TA5391
			142	170	8	16,0	Half	Divers	107TA5392
			105	140	10	18,5	Half	Hyster	129TA7561
5.00 S	12	7.00-12	149,3	203,2	5	32,0	Half	Yale - Hyster	129TA7562
			175	220	5	27,0	Half	Divers	107TA5393
			150	200	6	27,0	Half	Divers	107TA5394
			166	218	6	32,0	Half	Yale - Hyster	129TA7563
			170	220	6	27,0	Half	Divers	107TA5396
			170	220	6	32,0	Half	Divers	107TA5395
			145	190	8	26,0	Half	Toyota	107TA5397