



RESILIENT | ELITE XP

**DESIGNED TO PERFORM,
MADE TO EXCEL**

PERFORMANCE DEFINED

TIRE LIFE



Trelleborg products guarantee **the best wear** performance in the industry.

This results in longer tire life, **additional hours of usage**, reduced downtime and lower maintenance costs.

ENERGY SAVING



Trelleborg is the **largest approved tire manufacturer to the OEMs**. We work closely with them to ensure we meet the requirements of energy consumption.

This results in **reduced fuel costs** for our customers.

STABILITY



Trelleborg products are designed to have **large footprints** giving a maximum contact area leading to better stability and even tire wear.

COMFORT




Trelleborg understands the requirements of a **safe working environment**. Our products are designed to reduce vibration and **keep noise to a minimum level**.

We follow the strictest regulations for work safety while providing a comfortable ride.

PERFORMANCE AGAINST PREMIUM COMPETITOR


TIRE LIFE



ENERGY SAVING



STABILITY



COMFORT



TRELLEBORG ELITE XP

Trelleborg Elite XP delivers everything that today's material handling equipment requires – wear resistance, stability and driver comfort. Elite XP's unique design minimizes distortion increasing overall stiffness and confirms Elite XP as the tire of choice for the global materials handling industry. Elite XP's exceptional performance results from extensive R&D and testing processes, designed to create the tire that meets the ever increasing demands of industry today.



XP

Smooth

Counterbalanced Forklift Truck:
load capacity up to 25 km/h

Tire Size	Rim	Pattern	LOC Version	Width [mm]	Overall Diameter [mm]	Load Wheels [kg]	Steer Wheels [kg]	Other Vehicles: load capacity @ 10 km/h [kg]
4.00-8	3.00D-8	XP	Yes	104	406	950	730	865
15x4½-8	3.00D-8	XP	Yes	118	377	1040	800	945
5.00-8	3.00D-8	XP	Yes	122	457	1420	1090	1290
16x6-8	4.33R-8	XP	Yes	152	411	1495	1150	1360
18x7-8	4.33R-8	XP - Smooth	Yes	158	456	2145	1650	1950
140/55-9	4.00E-9	XP	Yes	132	380	1170	900	1065
6.00-9	4.00E-9	XP	Yes	141	524	1885	1450	1715
21x8-9	6.00E-9	XP	Yes	186	518	2760	2120	2505
6.50-10	5.00F-10	XP	Yes	160	574	2340	1800	2125
180/60-10	5.00F-10	XP	Yes	157	458	2405	1850	2185
200/50-10	6.50F-10	XP	Yes	197	456	2470	1900	2245
23x9-10	6.50F-10	XP	Yes	200	583	3445	2650	3130
7.00-12	5.00S-12	XP - Smooth	Yes	172	650	2915	2240	2645
23x10-12	8.00G-12	XP - Smooth	Yes	240	583	3770	2900	3425
27x10-12	8.00G-12	XP	Yes	240	676	3900	3000	3540
315/45-12	10.00G-12	XP	Yes	279	572	4485	3450	4075
23x5-13	3.75P-13	XP	Yes	138	617	1495	1150	1360
5.50-15	4.5-15	XP		143	664	2145	1650	1950
6.00-15	4.5-15	XP		150	694	2340	1800	2125
7.00-15	5.5-15	XP	Yes	180	730	3545	2725	3220
7.00-15	6.0-15	XP		180	730	3545	2725	3220
7.50-15	5.5/6.0/6.5-15	XP		194	745	3900	3000	3540
28x9-15	7.0-15	XP	Yes	225	692	3900	3000	3540
8.25-15	5.5-15	XP		207	808	4615	3550	4190
8.25-15	6.5-15	XP	Yes	207	808	4745	3650	4310
250-15	7.0-15	XP	Yes	225	711	4745	3650	4310
250-15	7.5-15	XP	Yes	238	712	4745	3650	4310
355/50-15 (28x12½-15)	9.75-15	XP	Yes	284	710	5690	4375	5165
300-15	8.0-15	XP	Yes	255	812	5850	4500	5310
355/65-15	9.75-15	XP	Yes	284	812	7800	6000	7080
9.00-20	6.5/7.0-20	XP		220	974	5400	4500	4905
10.00-20	7.5-20	XP - Smooth		250	1009	6000	5000	5450
10.00-20	8.0-20	XP		250	1009	6000	5000	5450
11.00-20	8.0-20	XP		260	1040	6540	5450	5945
12.00-20	8.0/8.5-20	XP - Smooth		260	1090	7560	6300	6870
12.00-20	10.0-20	XP		313	1090	7800	6500	7085
355/50-20	10.0-20	Smooth	Yes	310	834	8280	6900	7525
12.00-24	8.5-24	XP		295	1181	8040	6700	7305
12.00-24	10.0-24	XP		295	1181	9000	7500	8175
14.00-24	10.0-24	XP		331	1325	11100	9250	10085
16.00-25	11.25-25	XP		410	1445	15000	12500	13625

*In accordance to ETRTO Standard

AVAILABLE ADDITIONAL COMPOUNDS

NM
NON MARKING

ELCON

HL
HIGH LOAD

SCRUBBER

CR
CUT RESISTANT

